




SCALETRON™ SETS THE STANDARD
IN CORROSION RESISTANCE™

Model 4040 IBC™ Tote Bin Scale

- **Standard base sizes:** 24" x 24", 30" x 30", 36" x 36", 48" x 48", 60" x 60", 72" x 72" – custom sizes available
- **Net capacity:** Up to 10,000 lbs. (2268 kg) – custom capacities available
- **High accuracy of ±0.1% of capacity**
- **Single or multi-channel controllers with easy readability to 0.1 lb. (kg)**
- **Readout in pounds, kilograms, gallons or liters**



AccuPro 1000-1
Controller with
Keypad

AccuPro 1000-2
Controller with
Keypad

AccuPro 6000-TS
Controller with
Touch Screen

AccuPro 7000-TS
Controller with
Touch Screen

High Capacity Weighing Solution for Applications Requiring Frequent On/Off Loading of IBC Totes and Carboys

Model 4040 IBC is designed for weighing tote bins and carboys up to 72"x72". Featuring a four (4) load cell design, the scale base is ideal for high capacity applications requiring frequent on/off loading of containers. MADE IN USA.

Standard Features

- Rugged steel construction protected by a corrosion resistant, zinc oxide primed and dry powder epoxy coated finish, with solid 1/4" PVC decking for use in harsh environments
- Low profile platform (3.75" to 5.44") design increases safety and ease of container handling
- Accommodates off-center loads - containers can be placed anywhere on the scale platform and do not need to be leveled
- All hardware is stainless steel to prevent corrosion
- Four (4) NTEP approved stainless steel shear beam, temperature compensated load cells
- Electronic indicator housed in NEMA 4X, UL approved enclosure to provide protection from acids
- 20 ft. of 4 conductor wire cable

Available Controllers

- AccuPro 1000 Digital Controller with 1 or 2 channels, 4 button keypad and optional 4-20 mA output signal – scale or loop powered
- AccuPro 6000 Digital Controller with 1 or 2 channels, touch screen and 4-20 mA output signal – scale powered
- AccuPro 7000 Digital Controller with up to 4 channels, touch screen and 4-20 mA output signal – scale powered


Options

- High and low level set points
- 0-5V or 0-10V output signal
- Remote mounting of indicator box up to 200 feet away
- Seismic hold down brackets
- Stainless steel, ball-bearing bolt down feet (4)

Chemicals Weighed

- Alum, ammonia, caustic, fluoride, phosphate, polymers, sodium aluminate, sodium bisulfate, sodium hydroxide, sodium hypochlorite and other liquids or powders

Model 4040 IBC™ Tote Bin Scale Sizes & Specifications



Scale Base

PART NUMBER	4040 IBC-24	4040 IBC-30	4040 IBC-36	4040 IBC-48	4040 IBC-60	4040 IBC-72
Platform Length (A)	24" (610 mm)	30" (762 mm)	36" (914 mm)	48" (1219 mm)	60" (1524 mm)	72" (1829 mm)
Platform Width (B)	24" (610 mm)	30" (762 mm)	36" (914 mm)	48" (1219 mm)	60" (1524 mm)	72" (1829 mm)
Platform Height (C)	3.75" (95 mm) - add 1/2" for bolt down feet	3.75" (95 mm) - add 1/2" for bolt down feet	3.75" (95 mm) - add 1/2" for bolt down feet	4.75" (121 mm) - add 1/2" for bolt down feet	4.75" (121 mm) - add 1/2" for bolt down feet	5.44" (138 mm) - add 1/2" for bolt down feet
D	19.78" (503 mm)	26.37" (670 mm)	31.82" (808 mm)	44.62" (1133 mm)	58" (1473 mm)	65" (1651 mm)
E	20.75" (527 mm)	27.05" (687 mm)	36.42" (925 mm)	45.17" (1147 mm)	58" (1473 mm)	65" (1651 mm)
Net Capacity	Up to 1000 lbs. (454 kg) (150% overload protection)	Up to 1000 lbs. (454 kg) (150% overload protection)	Up to 2500 lbs. (1134 kg) (150% overload protection)	Up to 5000 lbs. (2268 kg) (150% overload protection)	Up to 8000 lbs. (3629 kg) (150% overload protection)	Up to 10,000 lbs. (4536 kg) (150% overload protection)
Weight	130 lbs.	150 lbs.	160 lbs.	240 lbs.	370 lbs.	545 lbs.

Digital Controllers

PART NUMBER	ACCUPRO 1000	ACCUPRO 6000-TS or 7000-TS
Interface	4 Button keypad	Touch screen
Accuracy	±0.1% to ±0.25% of full scale capacity	±0.1% to ±0.25% of full scale capacity
Display	1 Line x 6 character alphanumeric backlit LCD with 6 digits for weight	4.3" Graphic color LCD touch screen display with adjustable brightness
Display Items	Net weight and tare adjustment	Net and gross weight, % and bar graphs; mA out, tare adj., set points, 7000: data log, feed rate, daily usage, amount used, days till empty; batch net wt, batch and total amount, time
Channels	1 or 2 - One scale base per channel	Up to 4 - One scale base per channel
Output Signal	4-20mA Optional - scale or loop powered	4-20mA Optional - scale powered
Set Points		2 or 4 Per channel (high or low) - max. 8
Remote Option	Up to 200 feet from base frame	Up to 200 feet from base frame
Audible Alarm		Optional 78 dB internal piezo buzzer, external buzzer support
Communication Option		Modbus TCP or RTU
Power	90/240 VAC, 50/60Hz, 0.10/0.05A	100/277 VAC, 50/60 Hz, 0.10/0.05A
Weight	NEMA 4X, UL approved enclosure	NEMA 4X, UL approved enclosure
Enclosure	7lbs.	7lbs.